

# FIXATIVE BASE COATING D13

Indoor - Outdoor



Product Code: 143

## Description

Suitable primer for fixing and sealing unsound or porous masonry surfaces. It provides an easy application and adhesion of coatings, in aqueous dispersion: plaster, cement, fibrocement, concrete, bricks. Breathable. To fix or isolate size coatings or residues of these coatings.

## Technical Data

<b>Product Type</b>	Acrylic copolymer
<b>Finish</b>	Matt or semi-matt, depending on absorption
<b>Colour (UNE EN ISO 11664-4)</b>	Clear
<b>Density (UNE EN ISO 2811-1)</b>	0.80 - 0.85 Kg/l.
<b>Coverage (UNE 48282)</b>	Plaster: 1.2 - 1.5 m <sup>2</sup> /l , Concrete: 4 - 7 m <sup>2</sup> /l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	30 minutes
<b>Recoat time at 23°C 60% RH (UNE 48283)</b>	6 - 8 hours
<b>Methods of Application</b>	Brush and roller
<b>Equipment Cleaning</b>	Synthetics and Grease Thinner
<b>Application Temperature, RH&lt;80%</b>	-20°C - +40°C
<b>Flash Point (UNE EN ISO 3679)</b>	37 °C
<b>Volume Solids (UNE EN ISO 3233-3)</b>	13 - 14 %
<b>VOC (UNE EN ISO 11890-2)</b>	2004/42IIA (h)(750/750) Max. COV 700 g/l
<b>Pack sizes</b>	10 l and 4 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Thoroughly stir the contents in the pack. The surfaces have to be clean, dry and degreased.

### BARE SURFACES:

Apply as many coats as required to obtain the selected finish. In most cases, with just one single coat an excellent fixing of unsound surfaces is reached. It also prevents the effects of dirt on porous surfaces. With further coats, the finish will get more lustrous. Do not apply more than 3 coats.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2015-03

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

**TITAN**

143 - FIXATIVE BASE COATING D13

**INDUSTRIAS TITAN S.A.U.**

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

