

FIXATIVE BASE COATING D13

Indoor - Outdoor

TITAN



Product Code: 143

Description

Suitable primer for fixing and sealing unsound or porous masonry surfaces. It provides an easy application and adhesion of coatings, in aqueous dispersion: plaster, cement, fibrocement, concrete, bricks. Breathable. To fix or isolate size coatings or residues of these coatings.

Technical Data

Product Type	Acrylic copolymer
Finish	Matt or semi-matt, depending on absorption
Colour (UNE EN ISO 11664-4)	Clear
Density (UNE EN ISO 2811-1)	0.88 - 0.93 Kg/l.
Coverage	Plaster: 1.2 - 1.5 m ² /l , Concrete: 4 - 7 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	30 minutes
Recoat time at 23°C 60% RH (UNE 48283)	6 - 8 hours
Methods of Application	Brush and roller
Equipment Cleaning	Universal Thinner. Incompatible with White Spirit and mineral turpentine
Application Temperature, RH<80%	-20°C - +40°C
Flash Point (UNE EN ISO 3679)	37 °C
Volume Solids (UNE EN ISO 3233-3)	13 - 14 %
VOC (UNE EN ISO 11890-2)	2004/42IIA (h)(750/750) Max. COV 700 g/l
Pack sizes	10 l and 4 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Thoroughly stir the contents in the pack. The surfaces have to be clean, dry and degreased.

BARE SURFACES:

Apply as many coats as required to obtain the selected finish. In most cases, with just one single coat an excellent fixing of unsound surfaces is reached. It also prevents the effects of dirt on porous surfaces. With further coats, the finish will get more lustrous. Do not apply more than 3 coats.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original

unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-07

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscip. 210
N.I.F. B-08218158



AkzoNobel

