

MAXI GLOSS WAX

Indoor

TITAN



Product Code: 14D

Description

Easy-to-apply, odourless, high gloss protective wax. As a finish to protect and increase gloss, especially after applying TITAN TINTORETTO Venetian and "Calce" Stucco.

Protection of painted surfaces against dirt and stains.

Technical Data

Product Type	Wax
Finish	Gloss
Colour (UNE EN ISO 11664-4)	Clear
Density (UNE EN ISO 2811-1)	0.80 - 0.85 Kg./l.
Coverage	12 - 18 m ² /l.
Drying at 23°C 60 % RH (UNE 48301)	10 - 15 minutes
Methods of Application	Any suitable wax application tool
Thinner	TITAN White Spirit
Flash Point (UNE EN ISO 3679)	47 °C
Volume Solids (UNE EN ISO 3233-3)	28 - 30 %
Pack sizes	1 l and 250 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Evenly spread the wax on the whole surface by thin coats.. Once dry (after approx. 10 minutes), lightly rub with a clean rag until obtaining gloss.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

