

WATER BASED ACRYLIC FIXATIVE A19

Indoor - Outdoor.

TITAN

Product Code: 162 0001

Description

Fixative with high impregnation power. For sealing very porous surfaces, plaster, etc. It improves the paint adhesion on the surface. Moreover it avoids unevenness in the final finish because of irregular absorption areas.

Technical Data

Product Type	Pure acrylic
Colour (UNE EN ISO 11664-4)	Slightly whitish
Density (UNE EN ISO 2811-1)	1.030 - 1.05 Kg/l
Drying at 23°C 60 % RH (UNE 48301)	1 hour
Recoat time at 23°C 60% RH (UNE 48283)	4 hours
Methods of Application	Brush, roller and spray-gun
Thinning	400%
Thinner	Water
Equipment Cleaning	Water
Application Temperature, RH<80%	+5°C - +35°C
VOC (UNE EN ISO 11890-2)	2004/42/IIA (h) (50/30) Max. COV 29 g/l
Pack sizes	5 l and 1 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Carefully stir in the contents in the pack. The surfaces to be painted have to be clean, dry and in good condition. If the surfaces are in poor condition, repair all the damaged areas. Thoroughly remove all poorly adhered or inconsistent material. Get rid of any existing dirt and dust

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet. Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-07

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

162 0001 - WATER BASED ACRYLIC FIXATIVE A19

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

