

CHLORINATED RUBBER THINNER 872

TITAN



Product Code: 872

Description

Mixture of aromatic hydrocarbons with moderate-slow evaporation rate.

Fields of Application

Thinner suitable for alkyd and chlorinated-rubber topcoats and basecoats when a moderate evaporation rate is required. For example, when painting by brush or roller.

Technical Data

Density (UNE EN ISO 2811-1)	0,87 - 0,89 Kg/l
Flash Point (UNE EN ISO 3679)	32 °C
Pack sizes	5 l

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-11

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

872 - CHLORINATED RUBBER THINNER 872

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

