

CHLORINATED RUBBER THINNER 872



Product Code: 872

Description

Mixture of aromatic hydrocarbons with moderate-slow evaporation rate.

Fields of Application

Thinner suitable for alkyd and chlorinated-rubber topcoats and basecoats when a moderate evaporation rate is required. For example, when painting by brush or roller.

Technical Data

Density (UNE EN ISO 2811-1)	0.85 Kg/l
Flash Point (UNE EN ISO 3679)	32 °C
Pack sizes	20 l (minimum order 200 l) and 5 l

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2014-02

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

872 - CHLORINATED RUBBER THINNER 872

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

