

# ALKYD THINNER 875



**Product Code:** 875

## Description

Mixture of aromatic hydrocarbons of slow evaporation.

## Fields of Application

Thinner suitable for alkyd and oil paints. Due to its slow evaporation, it eases application by brush of alkyd and chlorinated-rubber coatings, in situations such as high temperature and strong wind.

## Technical Data

<b>Density (UNE EN ISO 2811-1)</b>	0.87 - 0.88 Kg/l
<b>Flash Point (UNE EN ISO 3679)</b>	38 °C
<b>Pack sizes</b>	20 l (minimum order 200 l) and 5 l

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2015-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



# TITAN

875 - ALKYD THINNER 875

**INDUSTRIAS TITAN S.A.U.**

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

