ALL PURPOSE THINNER 878

TITAN



Product Code: 878

Description

Quick-drying thinner. High thinning power.

Fields of Application

For thinning the following types of paints: quick-drying synthetic, epoxy, polyurethane and chlorinated rubber. It can be used as an anti blurr thinner, as a single product or combined with 874 Polyurethane Thinner.

Technical Data

Density (UNE EN ISO 2811-1)	0.85 - 0.88 Kg/l
Methods of Application	Brush, Roller and Spray-gun
Thinning	Brush: 5 - 10%, Spray-gun: 15 - 20%
Flash Point (UNE EN ISO 3679)	25 ºC
Pack sizes	11

Directions for use

GENERAL REMARKS:

It thins paints quickly. Therefore, it has to be used with care.

Especially suitable for paints to be applied by spray-gun. When applying alkyd paints by brush or roller, it is possible to use this thinner, but in limited amounts because it may damage base coats if they are not dry enough.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2016-04

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



