

# ALL PURPOSE THINNER 878



**Product Code:** 878

## Description

Quick-drying thinner. High thinning power.

## Fields of Application

For thinning the following types of paints: quick-drying synthetic, epoxy, polyurethane and chlorinated rubber. It can be used as an anti blurr thinner, as a single product or combined with 874 Polyurethane Thinner.

## Technical Data

<b>Density (UNE EN ISO 2811-1)</b>	0.85 - 0.88 Kg/l
<b>Methods of Application</b>	Brush, Roller and Spray-gun
<b>Thinning</b>	Brush: 5 - 10%, Spray-gun: 15 - 20%
<b>Flash Point (UNE EN ISO 3679)</b>	25 °C
<b>Pack sizes</b>	1 l

## Directions for use

### GENERAL REMARKS:

It thins paints quickly. Therefore, it has to be used with care.

Especially suitable for paints to be applied by spray-gun. When applying alkyd paints by brush or roller, it is possible to use this thinner, but in limited amounts because it may damage base coats if they are not dry enough.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2016-04

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



# TITAN

878 - ALL PURPOSE THINNER 878

### INDUSTRIAS TITAN S.A.U.

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

