

FIXATIVE UNDERCOAT H10

Indoor - Outdoor



Product Code: H10



Description

Water-based siloxane primer with high impregnation power. For indoor and outdoor application. Odourless. It allow the surface to breathe.

Fixative primer to seal surfaces which are highly absorbent, pulverulent, and with rests of previous paint in bad condition, highly burnt or with rests of old coats of low surface hardness, such as distemper paint, lime-based paints, plaster, etc.

It improves paint adhesion on support. Moreover it avoids unevenness in the final finish because of irregular absorption areas.

In outdoor application, it improves waterproofness and resistance to rain.

Especially suitable for plaster which is to be painted for the first time in order to ensure consistency of the future paint coats.

Technical Data

Product Type	Acrylic polysiloxane
Density (UNE EN ISO 2811-1)	0.90 - 1.10 Kg/l
Coverage	2 - 5 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	20 - 30 minutes
Recoat time at 23°C 60% RH (UNE 48283)	4 - 6 hour
Methods of Application	Roller, brush and spray-gun.
Thinner	Water
Application Temperature, RH<80%	+10°C - +30°C. Do not apply if rain is foreseen in the hours following application.
Volume Solids (UNE EN ISO 3233-3)	12.5 - 13.5%
VOC (UNE EN ISO 11890-2)	2004/42/IIA (h) (50/30) Mx. COV 0 g/l
Pack sizes	4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Carefully stir the contents in the pack. The surfaces to be painted have to be clean, dry and sound.

BARE SURFACES:

For surfaces in poor condition, remove poorly adhered and loose particles before applying the product. Remove dirt and dust off. If the surfaces are very porous, apply a first coat thinned with 20 - 30% water. Before drying, apply a second unthinned coat.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original

unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-09

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(España)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

