

STAIN ISOLATING PAINT H24

Indoor - Matt



Product Code: H24

Description

Water-based paint for indoor use. High coverage. Breathable and odourless. Especially recommended for isolating and covering dark stains on ceilings and walls caused by nicotine, kitchen oil and grease, fumes, soot, moulds, rust, markers, moist, etc. Ideal for inner application in premises where an odour-free paint is required and the rooms have to be immediately occupied: hospitals, bards, restaurants, kitchens, bathrooms, museums, churches, public use buildings, etc.

Technical Data

Product Type	Acrylic
Finish	Matt
Colour (UNE EN ISO 11664-4)	White
Density (UNE EN ISO 2811-1)	1.46 - 1.51 Kg/l
Coverage (UNE 48282)	8 - 10 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	30 - 60 minutes
Recoat time at 23°C 60% RH (UNE 48283)	6 - 8 hours
Methods of Application	Brush, roller and spray-gun.
Thinner	Ready-to-use. Do not thin.
Volume Solids (UNE EN ISO 3233-3)	38 - 40 %
VOC (UNE EN ISO 11890-2)	2.004/42IIA (a) (75/30) Max. COV 15 g/l
Pack sizes	4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Thoroughly stir the contents in the pack. Do not thin. The surfaces to be painted have to be clean, dry and sound. Do not mix it with other paints.

BARE SURFACES:

If the surfaces are in poor condition, repair all the damaged areas. Remove all poorly adhered or inconsistent material. Remove dirt and existing dust.

In order to strengthen the surface and achieve uniform porosity, as well as on distemper and size paints, whitewash or the surfaces where they were removed, it is recommended to previously apply a base coat of HIDROLIN Water-based Fixative or TITAN Water-based Sealing Primer.

It is not necessary to thoroughly remove grease stains or any other dirt. For a good isolating effect, two coats are recommended. It can also be used as an isolating primer and repainted with any kind of water-based paint.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Directly apply the paint after previously having washed or brushed. Do not thin.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Thoroughly remove old paints and proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2018-09

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

H24 - STAIN ISOLATING PAINT H24

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

