

COLOURLESS WATER REPELLENT PRODUCT H30

Indoors - Outdoors



Product Code: H30

Description

Colourless and transparent liquid with silicones. When drying it does not form any film and it does not change the normal appearance of the support. It protects the surface from the penetration of rain.

It also helps to maintain façades free from dust and dirt.

Wide application field: Façades and walls made out of stone, brickwork, concrete and, generally speaking, all neutral and alkaline materials commonly used in construction.

A previous test is required when applying a finishing coat.

Technical Data

| | |
|---|--|
| Product Type | Special silicone-based resins |
| Finish | It does not change the appearance of the surface |
| Colour (UNE EN ISO 11664-4) | Colourless |
| Density (UNE EN ISO 2811-1) | 0.79 Kg/l |
| Coverage | 3 - 10 m ² /l (In especially porous surfaces, it has to be applied up to saturation.) |
| Drying at 23°C 60 % RH (UNE 48301) | 2 hours |
| Recoat time at 23°C 60% RH (UNE 48283) | After 3 days |
| Methods of Application | Brush, Roller and Spray-gun. |
| Equipment Cleaning | Synthetics and Grease Thinner or White Spirit |
| Flash Point (UNE EN ISO 3679) | 39° C |
| Volume Solids (UNE EN ISO 3233-3) | 5 % |
| Pack sizes | 4 l and 750 ml. |

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Carefully stir the contents in the pack. Never thin the product.

The surfaces to be painted have to be clean, dry and in good condition.

BARE SURFACES:

Only in vertical surfaces or considerably inclined, the maximum efficiency will be reached with this kind of treatments.

The surfaces have to be dry when applying. If it has just rained, allow at least 24 hours before the application. If cleaned with high-pressure water jet, it is necessary to wait 3 days before the application.

It is recommended to fill up cracks of more than 0.5 m/m. with filler, mortar, etc. Moreover, remove all dirt and organic residues.

When applying on recently worked surfaces or new buildings, it is recommended to wait a month before the treatment.

On unsound, dusty surfaces or if there are incrustations, it is necessary to remove with a brush the elements with poor

adhesion.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-09

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

H30 - COLOURLESS WATER REPELLENT PRODUCT H30

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

