

PRESERVATIVE FOR PAINT FILMS H40



Product Code: H40

Description

Concentrated mixture of substances. It is used to enhance the preservation of emulsion paint films, especially when they are submitted to conditions which are favourable to mould growth.

Technical Data

Finish	Milky liquid
Density (UNE EN ISO 2811-1)	0.99 - 1.05 Kg/l
Mixing Rate	750 ml packs: 2 cap measures, 4 l: 10 cap measures or 1/3 of the bottle, 15 and 20 l: the whole content of the additive bottle, that is 250 ml
Pack sizes	250 ml

Directions for use

GENERAL REMARKS:

Shake the bottle before use.

Mix the suitable amount of additive. Carefully stir with a spatula or a stick until achieving a completely homogeneous mixture.

For shaking cans containing 15 - 20 litres or high viscosity paints, it is more convenient to use a mechanical shaker.

Finally, proceed to apply the paint following the directions for use.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2014-01

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

H40 - PRESERVATIVE FOR PAINT FILMS H40

INDUSTRIAS TITAN S.A.U.
España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94
Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

