

MOULD REMOVER H41



Product Code: H41



Description

Transparent liquid for removing moulds, algae and other organisms on walls and ceilings. Non-unpleasant odour. Indoors and outdoors. High penetration capacity in all kinds of masonry surfaces, ensuring their cleaning and disinfecting before painting. It is no bleaching product. For discolouring stains, conventional bleach can be used.

Technical Data

Finish	Transparent liquid
Density (UNE EN ISO 2811-1)	0.90 - 1.10 Kg/l
Recoat time at 23°C 60% RH (UNE 48283)	24 hours
Methods of Application	Brush, scourer or roller
Equipment Cleaning	Water
Pack sizes	750 ml

Directions for use

GENERAL REMARKS:

Shake before use.

Before applying the product, it is necessary to remove any excess of moulds, algae and other organisms in dry. After that, generously apply H41 Mould Remover without thinning. It is better to apply it in small areas and by means of brush or scourer, and suitably rubbing so that the product can reach the pores on the surface. For highly damaged supports, allow drying and proceed to a second application.

After 24 hours it can be overcoated with any kind of primer or paint, preferably containing anti-mould preservative and strictly following the directions for use.

H41 Mould Remover is not suitable as a paint additive.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2015-08

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158



H41 - MOULD REMOVER H41