

# SALTPETRE REMOVER H42



Product Code: H42



## Description

Product for removing and cleaning saltpetre and mould growth on masonry and brickwork surfaces.

For surfaces which are continuously exuding salt from the inside, such as contenting walls, it is advisable to waterproof them with H11 Saltpetre Barrier.

## Technical Data

<b>Finish</b>	Reddish transparent liquid
<b>Density (UNE EN ISO 2811-1)</b>	1.24 - 1.30 Kg/l
<b>Methods of Application</b>	Brush, roller, roller or sprayer
<b>Equipment Cleaning</b>	Water
<b>Pack sizes</b>	750 ml

## Directions for use

### GENERAL REMARKS:

Shake before use.

The H42 Saltpetre Remover is a concentrated product and only has to be used unthinned on very absorbent surfaces. For surfaces with poor absorption, thin with 50% water before using it.

Generously apply the product with brush, roller or spray. If the surface has much saltpetre or it is very absorbent, it is recommended to rub it with a brush soaked in the product. After that, proceed to a second application, thinning the product with 50% water.

Once applied, leave it to act for 1 hour and flush with water. If the saltpetre removing treatment is to be overcoated with paint, the surface has to be thoroughly dry, especially in the case of solvent-based paint.

This product is not effective on previously painted surfaces.

Avoid spilling the product on marble and mosaic. In case of spillage, wash and flush with plenty of water.

Use gloves during the handling and the application of the product

Do not apply at temperatures below 7°C

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2016-03

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

**TITAN**

H42 - SALTPETRE REMOVER H42

**INDUSTRIAS TITAN S.A.U.**

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

