

# ACUALUX GLOSS VARNISH

Indoor - Outdoor. Gloss



Product Code: J15

## Description

Acrylic permanent varnish with UV protective filter, to be applied as a topcoat over acrylic or latex-based paints. It is useful as a pore sealer for porous surfaces such as wood or plaster, at the thinning rate of 1 part of varnish and 3 parts of water. Good adhesive and varnish for paper techniques.

## Fields of Application

Properly thinned, it is an excellent pore sealer for absorbent surfaces such as wood, plaster, clay, etc. It improves the paint adhesion.

Suitable for protecting and/or modifying the final gloss level. It can be applied on ACUALUX and on other latex-based paints.

## Technical Data

<b>Finish</b>	Gloss
<b>Density (UNE EN ISO 2811-1)</b>	1.01 - 1.05 Kg/l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	20 - 30 minutes
<b>Methods of Application</b>	Brush and flat brush
<b>Thinner</b>	Water
<b>Equipment Cleaning</b>	Water
<b>Application Temperature, RH&lt;80%</b>	+10°C - +30°C. Do not apply if rain is foreseen in the hours following application.
<b>Pack sizes</b>	75 ml

## Directions for use

### GENERAL REMARKS:

Carefully stir the contents in the pot. Apply by thin coats, suitably thinned with water.

Porous surfaces, they have to be degreased, clean and dry.

Painted surfaces: they have to be dry.

It is advisable to previously test application before the final varnishing.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona  
(Espanya)  
Teléfono 934 842 500  
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210  
N.I.F. B-08218158



Salud  
Seguridad  
Medio Ambiente  
**Compromiso de Progreso  
de la Industria Química**



Salud  
Seguridad  
Medio Ambiente  
**Compromiso de Progreso  
de la Industria Química**