

# MINERAL PITCH ACUALUX



**Product Code:** J17

## Description

Required for artistic and handicraft tasks. This is the classical mineral pitch used for patinas, imitation of ageing or highlighting engraved metals, making frames and moulds more attractive and decorating objects.

## Fields of Application

Used in professional, artistic and handicraft tasks. Ideal for the application on wood, canvas, paper, cardboard, gypsum, plaster, brick, cement, stone, clay, steel and other metals.

## Technical Data

|   |  |
|---|--|
| <b>Finish</b>                             | Dark brown liquid. Gloss                                       |
| <b>Density (UNE EN ISO 2811-1)</b>        | 0.83 - 0.87 Kg/l   |
| <b>Drying at 23°C 60 % RH (UNE 48301)</b> | 1.15 - 1.45 h  |
| <b>Methods of Application</b>             | Paintbrush, brush, sponge, by hand, air brush or by immersion. |
| <b>Thinning</b>                           | Turpentine Oil or Petroleum Spirit.                            |
| <b>Equipment Cleaning</b>                 | Brush Cleaner.   |
| <b>Flash Point (UNE EN ISO 3679)</b>      | > 41 °C  |
| <b>Pack sizes</b>                         | 250 ml and 100 ml.   |

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Carefully shake the contents in the bottle. To be applied by very thin layers, directly on the above-mentioned kinds of surfaces or on dry paint (except for varnishes based on white spirit). If applied by too thick coats it can easily become brittle because of its extraordinary hardness.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona  
(Espanya)  
Teléfono 934 842 500  
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210  
N.I.F. B-08218158

