

ACUALUX CRACKING

Indoor. Gloss



Product Code: J18

Description

Water-based varnish, ideal for cracked effects and for obtaining an aged appearance.

Fields of Application

To be mostly applied on surfaces painted with acrylic and/or vinyl paints. Over the cracking varnish, spread a colour which is intended to form a contrast with the colour underneath. Special for creative and handicraft DIY.

Technical Data

| | |
|---|-------------------------|
| Finish | Gloss |
| Colour (UNE EN ISO 11664-4) | Clear |
| Density (UNE EN ISO 2811-1) | 1.01 - 1.03 Kg/l |
| Coverage (UNE 48282) | 7 - 9 m ² /l |
| Drying at 23°C 60 % RH (UNE 48301) | 45 - 60 minutes |
| Methods of Application | Brush or flat brush |
| Thinning | Water |
| Equipment Cleaning | Water |
| Volume Solids (UNE EN ISO 3233-3) | 7.5 - 8.5 % |
| Pack sizes | 75 ml |

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Apply the first layer of colour with the Acualux (Matt or Metallized). If the surface is very porous and in order to avoid absorption irregularities, apply an additional layer of paint. After that, spread the Acualux Cracking Varnish. Once dry, apply a new layer of colour, in order to produce a contrast with the first layer.

The thicker the final colour layer is, the more noticeable the cracking effect becomes. A previous test is strongly recommended.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products

TITAN

J18 - ACUALUX CRACKING

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

