

ACUALUX CRACKING

Indoor. Gloss



Product Code: J18

Description

Water-based varnish, ideal for cracked effects and for obtaining an aged appearance.

Fields of Application

To be mostly applied on surfaces painted with acrylic and/or vinyl paints. Over the cracking varnish, spread a colour which is intended to form a contrast with the colour underneath. Special for creative and handicraft DIY.

Technical Data

Finish	Gloss
Colour (UNE EN ISO 11664-4)	Clear
Density (UNE EN ISO 2811-1)	1.01 - 1.03 Kg/l
Coverage	7 - 9 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	45 - 60 minutes
Methods of Application	Brush or flat brush
Thinning	Water
Equipment Cleaning	Water
Volume Solids (UNE EN ISO 3233-3)	7.5 - 8.5 %
Pack sizes	75 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Apply the first layer of colour with the Acualux (Matt or Metallized). If the surface is very porous and in order to avoid absorption irregularities, apply an additional layer of paint. After that, spread the Acualux Cracking Varnish. Once dry, apply a new layer of colour, in order to produce a contrast with the first layer.

The thicker the final colour layer is, the more noticeable the cracking effect becomes. A previous test is strongly recommended.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscip. 210
N.I.F. B-08218158

