

ACUALUX FOTO TRANSFER



Product Code: J19

Description

Water-based varnish for the transfer of black and white or colour laser photocopies, especially on porous surfaces.

Fields of Application

Waterproof transfer gel which can also be used to give a finish topcoat.

Technical Data

Finish	Gloss
Density (UNE EN ISO 2811-1)	1.03 - 1.05 Kg/l
Drying at 23°C 60 % RH (UNE 48301)	30 - 60 minutes (for a wet thickness of 0.2 - 0.5 mm)
Methods of Application	Flat brush or spatula
Equipment Cleaning	Water
Pack sizes	75 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Thoroughly stir the product in the pack.

After having spread the gel, the printed side of the photocopy is to be attached face down onto the gel coated surface. Once the gel is dry, softly rub on the blank side of the photocopy with some water in order to remove the paper pulp and make the image appear perfectly transferred on the surface.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

