

CHALK PAINT

Indoor. Matt



Product Code: J20

Description

Water-based chalk finish, ultra matt and odourless paint. Vintage shades. Single coat. Easy-to-apply. No primer is needed on most surfaces. Very easy sanding and high levelling. Special for renewing and decorating wooden furniture and many other items made out of various materials. If TITAN Chalk Paint shades are combined with the auxiliary products of this range -varnish and wax-, and by using tools such as a sponge or a sanding file, it is possible to apply this paint in many ways in order to produce a wide variety of decorative effects. Thanks to its easy sanding, it is suitable to perform many stripping techniques and obtain shabby chic trendy looks.

By using Acualux Cracking Medium, colours can get a cracked look.

Fields of Application

Suitable for handicrafts on wood, linen, paper, concrete, stone, bisque, clay, plaster, expanded polystyrene, etc.

Technical Data

Finish	Matt.
Colour (UNE EN ISO 11664-4)	Colour card : 17 shades.
Density (UNE EN ISO 2811-1)	1.50 - 1.60 Kg/l (depending on colour)
Coverage (UNE 48282)	6 - 8 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	45 - 60 minutes
Recoat time at 23°C 60% RH (UNE 48283)	6 hours
Methods of Application	Brush, roller and air spray-gun.
Thinning	Water
Equipment Cleaning	Soap and water
Application Temperature, RH<80%	+10°C - +30°C
Pack sizes	750 ml and 150 ml.

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Certificates

**Seguridad de los juguetes. Migración de ciertos elementos UNE-EN 71-3
EU Environmental Label for indoor and outdoor paints and varnishes (Ecolabel)**

Directions for use

GENERAL REMARKS:

Carefully stir the contents in the pack. The surfaces have to be clean, dry and sound. Directly apply TITAN Chalk Paint. For wood with high tannin content, it is recommended to previously apply Multipurpose Water Based Primer.

STRIPPING with sandpaper

TITAN Chalk Paint is quickly and easily sandable. Apply your favorite colour on clean wood. Once dry, sand on the areas where the worn stripped effect is required. Firstly apply a base colour and then second coat in a shade which contrast with the base colour. When sanding, the background color will appear. The effect will vary depending on the sandpaper grade and the sanding depth. It is very important to sand only when the paint is thoroughly dry.

STRIPPING with wax

There are different kinds of worn stripped finishes. One of them is obtained by applying wax only on certain areas of a surface, which may be of virgin wood or a base coat of paint. Over this wax, spread another paint coat which will contrast with the base colour. When sanding, the paint applied over the wax will come off. Unlike the above-mentioned stripping effect with sandpaper, where the longitudinal sanding movement is noticeable, with this procedure the aged finish seems to emulate a paint peeling off. Rustic look.

DECOUPAGE with paper (Romantic floral style)

The shabby chic style shows soft colours combined with vintage fabrics and paper prints. Over an item coated with CHALK PAINT, you can stick découpage paper with our selected pattern. The TITAN Chalk Matt Varnish will act as a glue and also as a final varnish.

FINISH with wax

This topcoat finish on CHALK PAINT brings a truly vintage touch and appearance. Only furniture decorated in specialized handicraft workshops have this remarkable look. Chalk wax is applied by brush, cotton cloth or sponge on the items coated with TITAN Chalk Paint. Once dry, it is polished with a piece of cloth until the required gloss is obtained. If we want wax for an aged patina, previously mix it with some TITAN Mineral Pitch and apply it in the same way.

For renewing furniture submitted to frequent use, apply one topcoat of Matt Chalk Varnish to obtain extra protection.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products



TITAN

J20 - CHALK PAINT

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

