

# CHALK PAINT WAX

Colourless



Product Code: J25

## Description

Transparent and colourless creamy wax. It fixes and protects the applied paint. It provides a pleasant touch, as well as a unique handicraft looking finish.

## Technical Data

<b>Product Type</b>	Wax
<b>Colour (UNE EN ISO 11664-4)</b>	Colourless
<b>Density (UNE EN ISO 2811-1)</b>	0.74 - 0.78 Kg/l
<b>Coverage</b>	15 - 25 m <sup>2</sup> /l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	2 - 3 hours
<b>Methods of Application</b>	Rag, brush, cotton pad
<b>Thinner</b>	TITAN White Spirit or TITAN Petroleum Spirit
<b>Flash Point (UNE EN ISO 3679)</b>	>55 °C
<b>Volume Solids (UNE EN ISO 3233-3)</b>	22 - 25 %
<b>Pack sizes</b>	150 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Surfaces have to be clean and dry.

It is applied by brush with a rag. Let to dry for 2 - 3 hours and polish until obtaining the required gloss. It can also be used between two colour coats, to achieve certain stripping effects.

Mixed with TITAN Mineral Pitch, it becomes a patina wax for aged looks.

In view of the wide variety of surfaces and available techniques, it is always advisable to perform a test before application.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona  
(Espanya)  
Teléfono 934 842 500  
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210  
N.I.F. B-08218158

