

# DECORATION ECO FRIENDLY WATER BASED VARNISH MATT

Indoor - Outdoor



Product Code: M22

## Description

Quick drying matt water-based varnish. Resistant to household chemicals. Excellent blocking. Does not yellow. With anti-mould preservative. Great hardness, resistance and elasticity.

## Fields of Application

For the protection and decoration of all kinds of wooden surfaces.

## Technical Data

<b>Product Type</b>	Acrylic - polyurethane
<b>Finish</b>	Matt
<b>Colour (UNE EN ISO 11664-4)</b>	Clear
<b>Density (UNE EN ISO 2811-1)</b>	1,04 - 1,08 kg/l
<b>Coverage (UNE 48282)</b>	10 - 16 m <sup>2</sup> /l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	30 - 60 minutes / touch dry: 15 - 30 minutes
<b>Recoat time at 23°C 60% RH (UNE 48283)</b>	4 - 6 hours
<b>Methods of Application</b>	Brush and roller
<b>Thinning</b>	5% 1st coat for bare wood
<b>Thinner</b>	Water
<b>Application Temperature, RH&lt;80%</b>	+ 10 °C - + 30 °C
<b>Volume Solids (UNE EN ISO 3233-3)</b>	27 - 30%
<b>VOC (UNE EN ISO 11890-2)</b>	2.004/42IIA (e) (150/130) Max VOC 65 g/l
<b>Pack sizes</b>	2,5 l, 750 ml and 250 ml

## Certificates

Reaction to Fire UNE EN 13501-1: B-s2, d0 / On MDF substrate B-s1, d0

VOC ISO 16000-6 Emission: A +

Toy safety. Migration of certain elements UNE-EN 71-3

EU Ecolabel for interior and exterior paints and varnishes (Ecolabel)

## Directions for use

### GENERAL REMARKS:

Thoroughly stir the contents in the pack. The surfaces have to be smooth (sanded), degreased, clean and dry.

Apply by thin coats. Lightly sand between every two coats.  
The wood moisture content must not exceed 12% in hard wood and 15% in soft wood.  
Do not varnish under strong sunlight or with dew drops.

#### **BARE SURFACES:**

Sand the wood following the wood grain. Clean the surface, remove resin or resin secretion and smooth up sharp edges.  
Old bare Wood: It is essential to entirely remove the dried out, greyed surface by sanding or surfacing thoroughly until the wood in good condition is exposed.

Indoor wood: Apply 2 coats.

Outdoor wood: For improving the wood protection, apply one coat of Titanxyl Total Protection Ultra or Titanxyl Lasur Undercoat Ultra. Finish with 2 coats of Decoration Eco Friendly Water Based Varnish.

For restoring indoor wood with woodworm problems, apply one coat of Titanxyl Woodworm Treatment Plus, in case of mould apply a base coat of Titanxyl Total Protection Ultra or Titanxyl Lasur Undercoat Ultra.

Resinous and tropical wood: Drying can be difficult. Thoroughly degrease the wooden surface with TITAN Yate Thinner to remove resin.. Apply one varnish coat on a small area. Check if there is resin exudation. If this is the case, please refer to the Technical Service. If there is no resin exudation, finish with 2 - 3 coats of Decoration Eco Friendly Water Based Varnish.

#### **MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:**

Softly sand, dust off and apply 1 or 2 coats depending on the surface condition.

When old varnish coats are catalyzable or polyurethane-based, it is necessary to thoroughly sand the surface for removing them.

#### **MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:**

Thoroughly remove all previous coats and proceed as for bare surfaces.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Contains: IPBC to protect the initial properties of the treated article.

Issue date: 2020-03

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products



# TITAN

**INDUSTRIAS TITAN S.A.U.**  
España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94  
Portugal: Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764



M22 - DECORATION ECO FRIENDLY WATER BASED VARNISH MATT