

## Description

Soft odour water-based emulsion paint for painting walls and ceilings inside houses, industrial and business premises, etc. Snow white. Good coverage. Very easy-to apply. Breathable. It does not alter the permeability of the surfaces. It permits the passage of water vapour through the painted surface. Non drip.



Reaction to Fire



A+



White to be tinted



Low odour



Breathable



Non drip

## Technical Data

|  |   |
|--|---|
| Product Type                           | Acrylic styrene   |
| Finish                                 | Matt  |
| Colour (UNE EN ISO 11664-4)            | White   |
| Density (UNE EN ISO 2811-1)            | 1.57 - 1.63 Kg/l  |
| Coverage (UNE 48282)                   | 7 - 9 m <sup>2</sup> /l                                   |
| Drying at 23°C 60 % RH (UNE 48301)     | 20 - 40 minutes   |
| Recoat time at 23°C 60% RH (UNE 48283) | 6 - 8 hours   |
| Methods of Application                 | Brush, roller and airless                                 |
| Viscosity (UNE 48076)                  | 115 - 125 KU  |
| Thinner                                | Water   |
| Application Temperature, RH<80%        | +10°C - +30°C   |
| Tinting                                | TITAN Universal Colourant or Professional Water Based Dye |
| Volume Solids (UNE EN ISO 3233-3)      | 42 - 43 %   |
| VOC (UNE EN ISO 11890-2)               | 2004/42/IIA (a) (75/30) Max. VOC 5 g/l                    |
| Pack sizes                             | 15 l and 4 l  |

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Certificates

Reaction to Fire UNE EN 13501-1: B-s1, d0 / on substrate A2-s1, d0  
VOC Emission ISO 16000-6: A +

### Directions for use

#### GENERAL REMARKS:

Carefully stir the contents in the pack, manually or with low speed stirrer. The surfaces to be painted have to be clean, dry and sound. Do not apply on hot surfaces or in strong wind. A good diagnosis and support preparation are essential for obtaining the best results.

#### BARE SURFACES:

If the surfaces are in good condition, apply a first coat thinned with 10 - 15% water., Apply a second unthinned coat.

If the surfaces are in poor condition, repair all the damaged areas, remove all poorly adhered particles and material. Clean all existing dirt and dust.

In order to homogenise porosity and improve the finish, as well as on distemper and size paints, whitewash or the surfaces where these have been removed, it is recommended to apply a first coat of **S10 100% Acrylic All-Purpose Fixative** or **S50 Water-Based Sealing Primer**, following directions stated in the technical sheet.

#### MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

After washing or brushing the surface, directly apply a 10 - 15% water thinned first coat. Apply a second unthinned coat.

#### MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Thoroughly remove all previous paint coats and proceed as for bare surfaces.

### Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.