

## Descripción



Breathable



Low odour



Non drip



White to be tinted

## Datos técnicos

Naturaleza	Acrylic styrene
Acabado	Matt
Color (UNE EN ISO 11664-4)	White
Densidad (UNE EN ISO 2811-1)	1.57 - 1.63 Kg/l
Rendimiento	7 - 9 m <sup>2</sup> /l
Métodos de Aplicación	Brush, roller and airless
Viscosidad (UNE 48076)	115 - 125 KU
Diluyente	Water
Condiciones de Aplicación, HR<80%	+10°C - +30°C
Teñido	TITAN Universal Colourant or Professional Water Based Dye
Volumen Sólidos (UNE EN ISO 3233-3)	42 - 43 %
COV (UNE EN ISO 11890-2)	2004/42/IIA (a) (75/30) Max. VOC 5 g/l
Presentación	15 l and 4 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Certificaciones

Reaction to Fire UNE EN 13501-1: B-s1, d0 / on substrate A2-s1, d0  
VOC Emission ISO 16000-6: A +

### Modo de empleo

#### RECOMENDACIONES GENERALES:

Carefully stir the contents in the pack, manually or with low speed stirrer. The surfaces to be painted have to be clean, dry and sound. Do not apply on hot surfaces or in strong wind. A good diagnosis and support preparation are essential for obtaining the best results.

#### SUPERFICIES NO PREPARADAS:

If the surfaces are in good condition, apply a first coat thinned with 10 - 15% water., Apply a second unthinned coat.

If the surfaces are in poor condition, repair all the damaged areas, remove all poorly adhered particles and material. Clean all existing dirt and dust.

In order to homogenise porosity and improve the finish, as well as on distemper and size paints, whitewash or the surfaces where these have been removed, it is recommended to apply a first coat of S10 100% Acrylic All-Purpose Fixative or S50 Water-Based Sealing Primer, following directions stated in the technical sheet.

#### MANTENIMIENTO SUPERFICIES YA PINTADAS EN BUEN ESTADO

After washing or brushing the surface, directly apply a 10 - 15% water thinned first coat. Apply a second unthinned coat.

#### MANTENIMIENTO SUPERFICIES YA PINTADAS EN MAL ESTADO

Thoroughly remove all previous paint coats and proceed as for bare surfaces.

### Precauciones

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use. Paint reuse can effectively minimize environmental effects on the life cycle of products.

Fecha de actualización : 2021-05

Toda Ficha Técnica queda anulada automáticamente por otra de fecha posterior o a los cinco años de su edición. Garantizamos la calidad de nuestros productos pero declinamos toda responsabilidad debida a factores ajenos a la pintura o a una utilización inadecuada de la misma. Ante cualquier duda consulte a nuestros servicios técnicos a priori.