

Descripción



Certified coverage 98%



Suitable for overcoating & retouching



High wash resistance



White to be tinted + TitanColor Bases



Reaction to Fire

Datos técnicos

Naturaleza	Vinyl Veova
Acabado	Matt
Color (UNE EN ISO 11664-4)	White + TITANCOLOR Bases: Intermediate and Neutral
Densidad (UNE EN ISO 2811-1)	1.45 - 1.50 Kg/l
Rendimiento	10
Secado a 23°C 60 % HR (UNE 48301)	20
Repintado a 23°C 60% HR (UNE 48283)	6
Métodos de Aplicación	Brush, roller and airless
Viscosidad (UNE 48076)	115 - 125 KU
Diluyente	Water
Condiciones de Aplicación, HR<80%	+10°C - +30°C
Teñido	TITAN Universal Tinting Colours, Professional Water-Based Dye or TITANCOLOR System
Volumen Sólidos (UNE EN ISO 3233-3)	37 - 38 %
COV (UNE EN ISO 11890-2)	2004/42/IIA (a) (75/30) Max. VOC 15 g/l
Presentación	15 l and 4 l / TITANCOLOR Bases: 15 l, 4 l and 1 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Certificaciones

Determination of contrast ratio (Hiding Power) UNE EN ISO 6504-3: Class 2. 9.4 m²/l, (98% coverage rate)
Wet-scrub resistance UNE EN ISO 11998: Class 2 washability
Reaction to Fire: UNE EN 13501-1: B-s1, d0 /on A2-s1, d0 surface.
VOC emission ISO 16000-6:2006: A+

Modo de empleo

RECOMENDACIONES GENERALES:

Carefully stir the contents in the pack, manually or with low speed stirrer. The surfaces to be painted have to be clean, dry and sound. Do not apply on hot surfaces or in strong wind. A good diagnosis and support preparation are essential for obtaining the best results.

SUPERFÍCIES NO PREPARADAS:

If they are in good condition, apply a first coat thinned with 10 - 15% water.

Apply a second unthinned coat. If the surfaces are in poor condition, repair all the damaged areas. Remove old paints as well as all poorly adhered or inconsistent material. Clean dirt and existing dust.

In order to strengthen the surface and achieve uniform porosity, as well as on distemper and size paints, whitewash or surfaces where they have been removed, it is recommended to previously apply a base coat of S10 100% Acrylic All-Purpose Fixative or S50 Water-based Sealing Primer, following directions stated in the technical sheet.

MANTENIMIENTO SUPERFICIES YA PINTADAS EN BUEN ESTADO

After prior washing and sanding, directly apply a first coat thinned with 10 - 15% water. Apply a second unthinned coat.

MANTENIMIENTO SUPERFICIES YA PINTADAS EN MAL ESTADO

Thoroughly remove all previous paint coats and proceed as for non-prepared surfaces.

Precauciones

It contains BCM, IPU, IPBC, Terbutryn, to protect the initial properties of the treated article.

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use. Paint reuse can effectively minimize environmental effects on the life cycle of products.

Fecha de actualización : 2021-05

Toda Ficha Técnica queda anulada automáticamente por otra de fecha posterior o a los cinco años de su edición. Garantizamos la calidad de nuestros productos pero declinamos toda responsabilidad debida a factores ajenos a la pintura o a una utilización inadecuada de la misma. Ante cualquier duda consulte a nuestros servicios técnicos a priori.