

Descripción



Waterproof



Great hardness and resistance



Breathable

Datos técnicos

Naturaleza	Acrylic styrene / silicone
Acabado	Matt
Color (UNE EN ISO 11664-4)	White
Densidad (UNE EN ISO 2811-1)	1.50 - 1.60 Kg/l
Rendimiento	6 - 8 m ² /l (55 - 75 dry μ)
Secado a 23°C 60 % HR (UNE 48301)	4
Repintado a 23°C 60% HR (UNE 48283)	24
Métodos de Aplicación	Brush, roller and airless
Viscosidad (UNE 48076)	125 - 135 KU
Diluyente	Water.
Espesor Recomendado (UNE EN ISO 2808)	110 - 147 dry μ in 2 coats
Condiciones de Aplicación, HR<80%	+10°C - +30°C
Teñido	TITAN Universal Colourant or Water Based Professional Dye
Volumen Sólidos (UNE EN ISO 3233-3)	43 -44%
COV (UNE EN ISO 11890-2)	2.004/42/IIA (c) (75/40) Max. VOC 18 gr/l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Certificaciones

Permeability to liquid water UNE EN 1062-3: W3 Waterproof
Permeability to CO2 UNE EN 1062-6: C1 Anticarbonation
Permeability to water vapour UNE EN ISO 7783: Class 1. Breathable

Modo de empleo

RECOMENDACIONES GENERALES:

Carefully stir the contents in the pack, manually or with low speed stirrer. The surfaces to be painted have to be clean, dry and sound. Do not apply on hot surfaces or in strong wind. A good diagnosis and support preparation are essential for obtaining the best results.

SUPERFÍCIES NO PREPARADAS:

Surfaces in good condition: Apply a first coat thinned with 10-15% water. Once dry, apply a second unthinned coat.

Surfaces in poor condition: Repair all the damaged areas. Remove all poorly adhered or inconsistent material. Get rid of dirt and existing dust.

In order to strengthen the surface and achieve uniform porosity, as well as on distemper and size paints, whitewash or surfaces where they were removed, it is recommended to previously apply a base coat of S10 100% Acrylic All Purpose Fixative Primer or S20 Acrylic High Impregnation Acrylic Fixative, following the directions stated in the technical sheet.

MANTENIMIENTO SUPERFICIES YA PINTADAS EN BUEN ESTADO

Directly apply the paint after previously having washed or brushed the surface. Apply a first coat thinned with 5% water and a second unthinned coat.

In the event that previously applied paint is not breathable, it has to be removed, so that the system can reach its optimum properties.

MANTENIMIENTO SUPERFICIES YA PINTADAS EN MAL ESTADO

Thoroughly remove old paints and proceed as for bare surfaces.

Precauciones

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use. Paint reuse can effectively minimize environmental effects on the life cycle of products.

Fecha de actualización: 2024-03

Toda Ficha Técnica queda anulada automáticamente por otra de fecha posterior o a los cinco años de su edición. Garantizamos la calidad de nuestros productos pero declinamos toda responsabilidad debida a factores ajenos a la pintura o a una utilización inadecuada de la misma. Ante cualquier duda consulte a nuestros servicios técnicos a priori.