

## Description

Acrylic high covering primer, suitable for fixing and sealing very unsound or porous indoor surfaces. It provides an easy application and adhesion of paints and coatings. It also improves the topcoat look since it prevents absorption irregularities..Resistant to alkalis.



High coverage



Excellent adhesion



Snow white

## Technical Data

Product Type	Vinyl versatate
Finish	Matt
Colour (UNE EN ISO 11664-4)	White
Density (UNE EN ISO 2811-1)	1,58 - 1,62 Kg/l
Coverage (UNE 48282)	6 - 9 m <sup>2</sup>
Drying at 23°C 60 % RH (UNE 48301)	30 - 60 minutes
Recoat time at 23°C 60% RH (UNE 48283)	6 - 8 hours
Methods of Application	Brush, roller and airless
Thinner	Water
Application Temperature, RH<80%	+10°C - +30°C
Tinting	TITAN Universal Tinting Colours or TITAN Professional Water-Based Dye
Volume Solids (UNE EN ISO 3233-3)	46 - 47 %
VOC (UNE EN ISO 11890-2)	2004/42/IIA (a) (75/30) Max. VOC 20 g/l
Pack sizes	15 l and 4 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Thoroughly stir the contents in the pack, with a suitable tool or with a low speed mechanical mixer. The surfaces have to be clean, dry and sound. A good diagnosis and support preparation are essential to obtain the best results.

### BARE SURFACES:

If the surfaces are in good condition, apply a first coat thinned with 10 - 15% water. Apply a second unthinned coat.

If the surfaces are in poor condition, repair all the damaged areas, remove all poorly adhered particles and material. Clean all existing dirt and dust.

### Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.