

Descripción



Maximum performance



Recycled pack



Cradle to Cradle



Global Innovation

Datos técnicos

Naturaleza	Acrylic styrene (Biomass balance)
Color (UNE EN ISO 11664-4)	Clear
Densidad (UNE EN ISO 2811-1)	1.03 - 1.07 Kg/l
Rendimiento	6 - 10 m ² /l depending on surface porosity
Secado a 23°C 60 % HR (UNE 48301)	1
Repintado a 23°C 60% HR (UNE 48283)	4
Métodos de Aplicación	Brush, roller and airless
Dilucion	Up to 400% depending on the surface conditions
Diluyente	Water
Limpieza de Utensilios	Water
Condiciones de Aplicación, HR<80%	+10°C - +30°C. Do not apply if rain is foreseen in the next hours.
COV (UNE EN ISO 11890-2)	2004/42/IIA (h) (50/30) Max. VOC 0 g/l
Presentación	15 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Certificaciones

Cradle to Cradle Certified: GOLD (LEED Credits)

<https://www.c2ccertified.org/products/scorecard/p80-titan-natural-industrias-titan-s.a.u>

Modo de empleo

RECOMENDACIONES GENERALES:

Thoroughly stir the contents in the pack, with a suitable tool or with a low speed mechanical mixer. The surfaces have to be clean, dry and sound. Do not apply on warm surfaces or with strong wind. A good diagnosis and support preparation are essential to obtain the best results.

Apply 1 or 2 coats depending on the surface condition.

If the surfaces are in poor condition, repair all the damaged areas. Remove all poorly adhered or inconsistent material. Get rid of dirt and existing dust. On very porous surfaces, apply a first coat suitably thinned with water and, if required, a second coat.

Precauciones

Before applying the product on a large surface where scaffolding must be employed to lift more than two floor levels, it is essential to request the visit of a technician of the TITAN After-Sales Service, who will ensure that all details in our technical sheet are known, check the surface state, and provide on-site advice on environmental and atmospheric conditions in order to guarantee a perfect finish. If these directions are not observed, Industrias TITAN will not be held responsible for the success of the application.

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use. Paint reuse can effectively minimize environmental effects on the life cycle of products.

Fecha de actualización: 2024-03

Toda Ficha Técnica queda anulada automáticamente por otra de fecha posterior o a los cinco años de su edición. Garantizamos la calidad de nuestros productos pero declinamos toda responsabilidad debida a factores ajenos a la pintura o a una utilización inadecuada de la misma. Ante cualquier duda consulte a nuestros servicios técnicos a priori.