

RAL COLOUR ACRYLIC ENAMEL

Indoor - Outdoor. Gloss



Product Code: S00



Description

High quality spray acrylic enamel. Quick drying. High resistance outdoors, good colour retention and gloss. Excellent adhesion on a wide variety of materials.

Fields of Application

Decoration and protection of all kinds of wooden, metal, cardboard, stone, ceramics and many kinds of plastics. Ideal for industry, DIY, cars, plumbing, etc. **Unsuitable for application on expanded polystyrene.**

Technical Data

Product Type	Thermoplastic acrylic
Finish	Gloss
Colour (UNE EN ISO 11664-4)	RAL colour range
Coverage	400 ml spray can: 0.4 - 0.8 m ²
Drying at 23°C 60 % RH (UNE 48301)	30 minutes
Recoat time at 23°C 60% RH (UNE 48283)	Once it is dry to handle
Application Temperature, RH<80%	+10°C - +30°C
Pack sizes	400 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Shake spray can for 1 minute while hearing mixing balls. The surfaces to be painted have to be clean, dry and sound. Protect the surfaces not to be painted. Perform test spray on a non-visible area. Apply by thin crossed coats at a distance of 25 to 30 cm. Preferably spray two thin coats instead of one thick coats. In this way, better protection and a gloss smooth finish will be achieved.

BARE SURFACES:

Porous surfaces (plaster, wood, steel ...) First apply TITAN Spray White Rust Preventive Primer. This will seal pores and provide protection against rust. Then apply RAL Colour Spray Acrylic Enamel.

Non-porous surfaces (glass, painted surfaces...): remove dust, grease or dirt and directly apply RAL Colour Spray Acrylic Enamel.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Remove dust, grease and dirt and directly apply RAL Colour Spray Acrylic Enamel.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Remove all poorly adhered materials, smooth up the surface by sanding. Once clean, rust-free and dry, proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2016-07

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

