

FLUORESCENT PAINT

Indoor - Outdoor. Matt



Product Code: S05

Description

Top quality acrylic fluorescent paint. Excellent opacity. UV sun beams make this paint fade away, especially outdoors.

Fields of Application

For decoration, DIY and handicrafts on any previously primed material.

Technical Data

Product Type	Acrylic
Finish	Typical bright matt
Colour (UNE EN ISO 11664-4)	Colour range
Coverage	200 ml can: 0.2 - 0.4 m ² / 400 ml can: 0,4 - 0,8 m ²
Drying at 23°C 60 % RH (UNE 48301)	30 minutes
Recoat time at 23°C 60% RH (UNE 48283)	2 hours
Application Temperature, RH<80%	+10°C - +30°C
Pack sizes	400 ml and 200 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Shake the spray can for one minute while hearing the mixing balls. The surfaces to be painted have to be clean, dry and free from rust and grease.

Apply by thin crossed coats from a distance of 25 to 30 cm. Apply two thin coats instead of one thick coat. Improved protection and a smoother finish will be achieved.

Protect the surfaces that are not to be painted. Perform a test spray on a non-visible area.

If used outdoors, the typical bright and colour gradually fade away in direct proportion with the exposition time to direct sunlight. However, the original painted appearance can be restored by applying the fluorescent paint on the aged surface again.

BARE SURFACES:

On clean and dry surfaces, previously apply the Spray White Rust-Preventive Primer in order to enhance fluorescence with the reflection of the light going through the Fluorescent Paint.

On paper, cardboard, carton or some white fabric, it is not necessary to prime the surface with Spray White Rust-Preventive Primer. Fluorescent Paint can be directly applied.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

On previously painted surfaces and in good condition, lightly sand, apply a base coat of TITAN Spray White Primer and finish with the Fluorescent Paint in the required shade.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Remove all poorly adhered materials, smooth up the surface by sanding. Once clean, rust-free and dry, proceed as for bare

surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

