

METALLIZED ENAMEL

Indoors - Outdoors. Satin



Product Code: S08

Description

Quick-drying enamel with high quality metallized effect pigments. Deep and vivid colours. Good resistance to impact and scratches. Good flexibility.
Unsuitable for permanent contact with gasoline.

Fields of Application

Decoration, DIY and handicrafts on metal, glass, cardboard, stone, ceramics and some plastics.
With a suitable primer, it can be used on items made of wood, plaster, bisque and other porous materials. With one single base coat, a beautiful metallic glazing effect is achieved.

Technical Data

Product Type	Acrylic
Finish	Metallic
Colour (UNE EN ISO 11664-4)	Color range
Drying at 23°C 60 % RH (UNE 48301)	15 - 30 minutes
Recoat time at 23°C 60% RH (UNE 48283)	24 hours.
Application Temperature, RH<80%	+10°C - +30°C
Pack sizes	Silver and yellow gold: 400 ml and 200 ml / Other colors: 200ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Shake the spray can for one minutes while hearing mixing balls. The surfaces to be painted have to be clean, dry and sound. Protect the surfaces that are not to be painted. Perform a test spray on a non-visible area. Apply by crossed thin coats at a distance of 25 to 30 cm. Apply two thin coats instead of one thick coat. In this way, a better protection and a smooth, gloss finish will be achieved.

BARE SURFACES:

Previously apply a base coat of Spray White Rust-Preventive Primer in order to ensure a good adhesion of the enamel coat. Apply the Spray Metallized Enamel once the primer is dry.
In order to mask colours contrast with the original ñpaint, it is advisable to thoroughly coat the whole primed area and even exceed its outline.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Remove dust, grease or dirt and directly apply Spray Metallized Enamel.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Remove all poorly adhered materials, smooth up the surface by sanding and, once clean, rust-free and dry, proceed as for non-prepared surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

