

STAIN-COVERING PAINT

Indoors - Outdoors. Matt



Product Code: S10

Description

Isolating quick-drying primer for restoring works, both indoors and outdoors.

Thixotropic formula which allows excellent results, even on vertical surfaces. Very easy application thanks to its 360° diffuser valve.

Fields of Application

Isolating primer for stains such as grease, soot, nicotine, moist, etc.

It is also very suitable as a primer for very porous surfaces such as wood, conglomerated, plaster and concrete. It can also be used as a primer to be overcoated with wallpaper on plaster board or agglomerated material.

Technical Data

Product Type	Polyvinyl
Finish	Matt
Colour (UNE EN ISO 11664-4)	White
Density (UNE EN ISO 2811-1)	500 ml can: 1 m2
Drying at 23°C 60 % RH (UNE 48301)	5 minutes
Recoat time at 23°C 60% RH (UNE 48283)	After 15 minutes
Application Temperature, RH<80%	+10°C - +30°C
Pack sizes	500 ml.

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Shake the spray can for 1 minute while hearing the mixing balls. The surfaces to be painted have to be clean, dry and sound.

Apply by thin crossed coats at a distance of 25 to 30 cm. Apply two thin coats instead of one thick coat. An improved protection and a smoother finish will be achieved.

One first coat isolates water marks, grease, soot and nicotine stains. A second coat provides an excellent opacity.

Finish with any product of our range of paints for walls and ceilings.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-08

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscip. 210
N.I.F. B-08218158



S10 - STAIN-COVERING PAINT