

CHROME EFFECT ENAMEL

Indoor. Gloss



Product Code: S12



Description

High quality bright gloss metallic-looking enamel. Decorative effect. It provides an appearance similar to chrome or metallic gold. Limited resistance to abrasion and weathering.

Fields of Application

Decoration and handicrafts on wood, metal, cardboard, stone, glass, ceramics and some plastics.

Technical Data

Product Type	Hydrocarbon resin
Finish	Metallic (high gloss)
Colour (UNE EN ISO 11664-4)	Silver and gold
Coverage	200 ml spray can: 0.5 m ² , 400 ml spray can: 1 m ²
Drying at 23°C 60 % RH (UNE 48301)	1 hour
Recoat time at 23°C 60% RH (UNE 48283)	24 hours
Application Temperature, RH<80%	+10°C - +30°C
Pack sizes	200 ml and 400 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Shake the spray can for 1 minute while hearing the mixing balls. The surfaces to be painted have to be clean, dry and sound. Protect the surfaces that are not to be painted. Perform test spray on a non-visible area.

Apply by thin and crossed coats from a distance of 25 to 30 cm. Apply two thin coats instead of one thick coat. A better protection and a smooth gloss finish will be achieved. In contact with thinners, grease and even hand sweat, it easily turns greyish. However, if the sprayed surface has to be submitted to weathering for a short time or it has to stand a certain degree of handling, the Spray Chrome Effect Enamel, once dry, can be overcoated with Spray Protective Varnish for Chrome Effect. This varnish provides better resistance to weathering and handling but it implies a certain alteration in the surface look. A previous test is advisable.

BARE SURFACES:

It is important to previously apply one coat of Spray Rust-Preventive White Primer in order to ensure good adhesion of the whole coating. Apply the Spray White Enamel for Electrical Appliances once the primer is hard dry. In order to reduce colour contrast with the original paint, it is advisable to coat the whole primed surface and preferably exceeding its outline.

Porous surfaces (plaster, wood, steel ...), first apply the Spray White Rust-Preventive Primer in order to seal pores. Then apply the selected shade of the Chrome Effect Enamel.

Non porous surfaces (glass, painted surfaces...): Remove any dust, grease or dirt and directly spray the Chrome Effect Enamel.

Polystyrene: Previously apply TITAN Spray Lacquer Gum.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Remove dust, grease or dirt and directly apply Chrome Effect Enamel.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Remove all poorly adhered materials. Smooth up the surface by sanding. Once dry, rust-free and dry, proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-08

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

