

PAINT FOR SIGNALLING AND MARKING

Indoor - Outdoor. Fluorescent matt



Product Code: S21

Description

Fluorescent acrylic high quality paint. High contrast. Once dry, it is very easily seen. It dries quickly and allows remarking at any time if required.

To obtain the best fluorescent effect, this paint is much more effective on white surfaces.

The special design of this marking spray paint allows using the can upright or upside down. It can be used for marking floors, walls and ceilings. Innovative safety valve, which can be blocked to avoid unwanted pressing.

The marks will gradually disappear with the degrading effect of UV sunbeams as well as for the wear or use on the marked area.

Fields of Application

For provisional marks in constructions works, pipe laying, on road, for industrial uses, non-permanent marking on trees, reference points for topographic signalling, tunnels, telecommunications, temporal marking of limits and areas in sport facilities, etc.

To be applied on stone, concrete, iron, sand, earth, grass (*), wood, cork, asphalt, plastic and the usual construction materials. It can be applied on dry, wet or moistened surfaces.

(*) Previously test the grass type resistance to this product.

Technical Data

Product Type	Acrylic
Finish	Typical fluorescent matt
Colour (UNE EN ISO 11664-4)	Colour range
Drying at 23°C 60 % RH (UNE 48301)	10 minutes
Recoat time at 23°C 60% RH (UNE 48283)	30 minutes
Application Temperature, RH<80%	+10°C - +30°C
Pack sizes	500 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Shake the spray can for 1 minute while hearing the mixing balls. The surfaces to be painted have to be clean, dry and sound. Protect the surfaces that are not to be painted. Perform a spray test on a non-visible area.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to

avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-08

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

S21 - PAINT FOR SIGNALLING AND MARKING

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

