

METAL PROTECTIVE VARNISH



Product Code: S40

Description

Glossy, hardwearing high adhesion varnish. It protects metals from rust, blackening, moist. ageing and wear damage. It is also suitable for metal items in yachting because of its high resistance to marine environments. It contains UV filters.

Fields of Application

Suitable for copper, tin, bronze, aluminium and silver, both indoors and outdoors.

Technical Data

| | |
|---|---|
| Product Type | Acrylic |
| Finish | Gloss |
| Colour (UNE EN ISO 11664-4) | Clear |
| Coverage | 200 ml. can: 0.2 - 0.4 m ² / 400 ml. can: 0.4 - 0.8 m ² |
| Drying at 23°C 60 % RH (UNE 48301) | 50 minutes |
| Recoat time at 23°C 60% RH (UNE 48283) | 1 hour |
| Application Temperature, RH<80% | +10°C - +30°C |
| Pack sizes | 400 ml and 200 ml |

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Shake the spray can for 1 minute while hearing the mixing balls.

In order to obtain the most beautiful varnished finish, the metal surface has to be polished smooth and gloss. Before application, degrease and remove the existing dirt from the surface to be varnished.

Apply by thin crossed coats at a distance of 25 to 30 cm.

One first varnish coat will keep the metal unvarnished appearance (texture and gloss differences). A higher number of coats will result in glossier finishes.

On old surfaces which show damage or are previously varnished or painted, it is advisable to remove old damaged coats depending on the required finish and polish again, if necessary.

If it is foreseen than the item may suffer rust during the application process. you can apply the protective varnish in the different restoration steps. When finishing it, the required top coat has to be applied following the instructions for new bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to

avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-08

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscip. 210
N.I.F. B-08218158

