

CLEAR SPECIAL VARNISH FOR METALLIZED SURFACES



Product Code: S44

Description

High quality acrylic varnish. When applied on the Spray Metallized Enamel, it produces an extraordinary gloss, similar to a two-component finish.

Weather resistant and non-yellowing. It resists stains of fuel and mineral grease and oils. It allows being washed with detergents and water. It does not allow being washed with petrol.

Fields of Application

Indoors and outdoors. To improve gloss and lightness of paints with metallized look; both for aged original colours (because of sun, rain, etc.) and for new colours when a glossier finish is required.

Technical Data

Product Type	Acrylic
Finish	Gloss
Colour (UNE EN ISO 11664-4)	Clear
Coverage (UNE 48282)	200 ml. can: 0.5 m ²
Application Temperature, RH<80%	+10°C - +30°C
Pack sizes	200 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Shake the spray can for 1 minute while hearing the mixing balls. The surfaces to be painted have to be clean, dry and sound.

Apply by crossed coats at a distance of 25 to 30 cm

Pay attention to the colour alteration after the varnish application because intensity is increased.

Previously test compatibility in order to avoid adhesion problems or other unwanted alterations.

For surfaces which are freshly painted with acryl-based enamels, directly apply Special Varnish for Metallized Surfaces.

On aged surfaces, with loss of original gloss, it is recommended to homogenise the object by a light water sanding with no. 360/400 sandpaper. Make circular motions in order to avoid sand scratching marks. After that, dust off and apply one or two coats of Special Varnish for Metallized Surfaces.

The varnished surface can be polished after having dried for 24 hours.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2018-08

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

S44 - CLEAR SPECIAL VARNISH FOR METALLIZED SURFACES

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

