

# CHROME EFFECT PROTECTIVE VARNISH



**Product Code:** S47

## Description

High quality acrylic varnish. It protects the items coated with Chrome-Effect Metallized Spray Paint, from the damage caused by weathering and handling.

## Technical Data

<b>Product Type</b>	Acrylic
<b>Finish</b>	Gloss
<b>Colour (UNE EN ISO 11664-4)</b>	Clear
<b>Coverage</b>	0.5 m2 per 200 ml. can
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	30 minutes
<b>Recoat time at 23°C 60% RH (UNE 48283)</b>	2 hours
<b>Application Temperature, RH&lt;80%</b>	+10°C - +30°C
<b>Pack sizes</b>	200 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Shake the spray can for 1 minute while hearing the mixing balls. The surfaces to be coated have to be clean, dry and sound.

Protect the surfaces that are not to be coated. Perform a spray test on a non-visible area. Pay attention: when varnishing the surface, the mirror effect can suffer alterations.

Apply by thin and crossed coats at a distance of 25 to 30 cm. Apply two coats instead of one single coats. Improved protection and a glossier and smoother finish will be achieved.

Take care not to stain the surfaces to be protected and keep them away from hand sweat because these irregularities would be noticeable after applying the protective varnish.

Do not sand or polish the paint to be protected with any rag or similar. It has to be kept with an appearance as similar to the original as possible, but with an increased resistance to weathering and handling.

Leave to dry before applying a second coat.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-08

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona  
(Espanya)  
Teléfono 934 842 500  
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210  
N.I.F. B-08218158

