

RUST PREVENTIVE PRIMER

Indoor - Outdoor



Product Code: S60



Description

High quality, acrylic quick-drying primer. It guarantees an excellent adhesion for topcoats such as acrylic paint, synthetic or multi-combi paints. Easy sanding.

Fields of Application

As a general use rust-preventive primer in moderate corrosion environments, on iron structures and items, both indoors and outdoors, where specially short overcoating intervals are required.

Technical Data

Product Type	Acrylic
Finish	Matt
Colour (UNE EN ISO 11664-4)	Grey and oxide red
Coverage	200 ml. can: 0.5 m2
Drying at 23°C 60 % RH (UNE 48301)	30 minutes
Recoat time at 23°C 60% RH (UNE 48283)	After 24 hours
Application Temperature, RH<80%	+10°C - +30°C
Pack sizes	200 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Shake the spray for 1 minute while hearing the mixing balls. The surfaces to be painted have to be clean, dry and sound.

Apply by thin crossed coats from a distance of 25 to 30 cm.

Apply two thin coats instead of one thick coat. Improved protection and a smoother finish will be achieved.

BARE SURFACES:

Steel: Remove rust with a wire brush or a sanding tool. Degrease, remove dust and rust residues.

Other surfaces: Seek advice.

Low corrosion environments: 1 crossed coat.

Moderate corrosion environments: 2 - 3 crossed coats.

Apply a topcoat of any of our spray paints.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

When restoring an item with old paint coats in poor condition or showing rust, dirt, mechanical damage, etc. it is necessary to remove all previous coats and rust residues with moistened nº. 180/200 sandpaper. After having dried and cleaned the item, proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-08

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(España)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

