

# GRAFFITI REMOVER



**Product Code:** S80



## Description

It is a product for removing most paint stains and marks made by graffiti on several kinds of surfaces: masonry and stone walls, glass objects, metal, urban furniture, some plastics and other materials.

## Technical Data

<b>Product Type</b>	Thixotropic organic solvents
<b>Colour (UNE EN ISO 11664-4)</b>	Clear
<b>Coverage</b>	400 ml can: 0.6 - 1 m2, depending on the use and treated surface.
<b>Application Temperature, RH&lt;80%</b>	+10°C - +30°C
<b>Pack sizes</b>	400 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Shake the spray can for 1 minute while hearing the mixing balls. The surfaces have to be clean, dry and sound.

Firstly, carefully evaluate the kind of surface to be cleaned. Before application test the resistance of the surface to the cleaning procedure, especially with some plastics and certain paints.

Protect the surfaces that are not to be cleaned. Perform a spray test on a non-visible area. The Graffiti Remover can alter the original appearance of some plastic or painted surfaces.

Apply a thick coat and let the product to act for 10 - 15 minutes. Depending on the kind or the thickness of the graffiti to be removed, it may be necessary to let the product to act for several hours.

Before applying new coatings on the surface, remove all residues of Graffiti Remover with water and a scourer or with cleaning solvent.

On non-porous surfaces, such as glass, metal, tile and vitrified elements, some marbles, two-component paints, follow this procedure: Spray at a distance of 20 -25 cm. Remove by carefully rubbing with a brush and rinse with plenty of water.

On porous surfaces. For instance in brick and masonry walls, some stones, marble, bare wood, textured walls etc. It is necessary to follow the previous procedure, but finishing with water jet so that the Graffiti Remover can easily reach the pores and irregularities of the surface.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-08

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona  
(Espanya)  
Teléfono 934 842 500  
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210  
N.I.F. B-08218158

