

SPRAY MATT PICTURE VARNISH



Product Code: S91 0014



Description

Matt finish varnish. Long-lasting. Non-yellowing. Quick-drying. Lightfast. Resistant to UV rays. Permanent paleness. It protects pictures against grease, dust and air pollution. Elastic. Non-cracking.

Fields of Application

To be used for varnishing pictures painted with oil or acrylic colours.

Technical Data

Product Type	Acrylic
Finish	Matt
Density (UNE EN ISO 2811-1)	0.76 - 0.78 Kg/l
Coverage (UNE 48282)	400 ml spray can: 0.8 - 1.2 m2
Drying at 23°C 60 % RH (UNE 48301)	Touch dry: 2 hours / Hard dry: 24 hours
Pack sizes	200 ml and 400 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Shake the spray can for 3 minutes.

Do not spray over surfaces painted with synthetic resin lacquer.

Previously test in order to see if the product is suitable for the application intended.

Directly apply by thin coats on thoroughly dry colours. Apply at a distance of 20 cm. from the surface to be protected. Spray from side to side by thin and quick coats and surpassing the outer edge of the work. Then vertically spray in order to uniformly spread the Picture Varnish on the whole surface.

Do not insist on any areas. It is better to apply a new coat after 24 hours or when it is completely dry.

On old artworks: If they are previously varnished damaged works and/or with new paint layers, before applying the Picture Varnish, it will be necessary to clean the work carefully and to completely restore the whole damaged area.

Once the work is in good condition and hard dry, the Picture Varnish can be applied to protect the work such as it were new.

This varnish is reversible. If required, it can be completely removed by rubbing the surface with a soft cloth moistened with petroleum spirit (white spirit) or turpentine oil, and well drained.

The optical change (gloss reduction) may alter the contrast and the depth of the painted items.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2015-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

S91 0014 - SPRAY MATT PICTURE VARNISH

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

