

SPRAY TITAN SHELLAC



Product Code: S91 0045

Description

Used as a primer for porous surfaces, such as plaster or wood, in order to avoid excessive absorption. It is also an excellent varnish with a high gloss finish. It dries by evaporation.

Fields of Application

Highly used by artisans and craftsmen, and also very popular for handicraft jobs.

On wood: highlights the grain and provides hardness and gloss.

On plaster: Eliminates excessive porosity and highlights the liveliness of the colours applied.

Technical Data

Finish	Gloss
Drying at 23°C 60 % RH (UNE 48301)	30 minutes - 2 hours
Equipment Cleaning	Brush Cleaner
Pack sizes	200 ml and 400 ml

Directions for use

GENERAL REMARKS:

On plaster or other porous surfaces, acting as a primer, apply one or two coats. It can also be used as a gloss finish varnish.

On wood: If the wood is new, the surface has to be sanded, clean and dry. Then apply 3 or 4 coats. Let to completely dry between every two coats.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2016-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

S91 0045 - SPRAY TITAN SHELLAC

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

