

ACRITÓN ACRIFIX 002

Indoor - Outdoor



Product Code: T30700



Description

Acrylic primer with very fine particles (0.02 μ). Because of its high penetration and adhesion power, it is suitable for priming and sealing porous surfaces in façades.

- * Excellent penetrating and sealing performance on plaster and concrete surfaces.
- * It reinforces the outer coat surface.
- * It allows adhesion of water-based finish paints on the surface to be coated.
- * Resistant to surface alkalinity and saltiness.
- * Breathable.
- * Easy cleaning and application

Fields of Application

Suitable for reinforcing unsound surfaces, both indoors and outdoors, prior to the suitable application of finish paints and coatings.

Technical Data

Product Type	Pure acrylic
Finish	Satin/Matt, depending on the surface absorption
Colour (UNE EN ISO 11664-4)	Colourless
Density (UNE EN ISO 2811-1)	1.01 - 1.05 Kg/l
Coverage	6 -10 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	1/2 - 1 hours
Recoat time at 23°C 60% RH (UNE 48283)	4 - 6 hours
Methods of Application	Brush, roller, spray-gun
Thinner	Water
Equipment Cleaning	Clean equipment with water immediately after use
Application Temperature, RH<80%	+10 °C - +30 °C. Do not apply if rain is foreseen in the next hours.
Volume Solids (UNE EN ISO 3233-3)	27 \pm 1 %
VOC (UNE EN ISO 11890-2)	2.004/42/IIA (h) (50/30) Máx. COV 0 g/l
Pack sizes	20 l, 5 l and 1 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Thoroughly homogenise the content in the pack. The surface has to be dry and free from any dust, grease, saltpetre, mould, moss, etc.

BARE SURFACES:

Firstly, degrease the surface to be painted and remove the rests of concrete, sand, etc. by brushing. After removing all residues on the surface, apply one thinned coat (1 part of Acrifix 0,02 : 1 part of water). If required, apply a second coat, also thinned.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2015-07

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(España)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

