

ENVIRONMENTALLY-FRIENDLY WAX-LIKE ASPECT VARNISH

Indoor - Outdoor. Satin



Product Code: V38

Description

Alkyd, clear wax-like varnish for decorating and protecting all kinds of wood structures indoors and outdoors. High build and soft touch satin finish. Quick drying; it neither drips nor sags. Hard and flexible. It contains special stabilizers for obtaining a highly resistant and long-lasting finish. Odour free.

Technical Data

Product Type	Urethaned alkyd
Finish	Satin
Colour (UNE EN ISO 11664-4)	Clear
Density (UNE EN ISO 2811-1)	1.03 - 1.05 Kg/l
Coverage (UNE 48282)	10 - 12 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	3 - 4 hours
Recoat time at 23°C 60% RH (UNE 48283)	24 hours
Methods of Application	Brush, roller and spray-gun
Thinning	Brush 5% (1st coat: bare wood), Roller 5%, Spray-gun: 10%.
Thinner	Water
Equipment Cleaning	Water
Application Temperature, RH<80%	+10°C - +30°C. Do not apply if rain is foreseen in the next hours.
Volume Solids (UNE EN ISO 3233-3)	35 - 37%
VOC (UNE EN ISO 11890-2)	2004/42IIA (e) (150/130) Max. COV 44 g/l
Pack sizes	2.5 l, 500 ml and 250 ml.

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Carefully stir the contents in the pack and apply by thin coats on smooth (sanded), clean and dry surfaces, thinning if required.

BARE SURFACES:

Softly sand between every two coats to obtain a perfect finish.

Between every two coats, it is advisable to carefully rub the applied surface with synthetic abrasive fibre (such as Scotch Brite Fine), moistened with water. Dry with a piece of cloth before varnishing again.

For tropical or resinous wood: Please refer to the Technical Service.

Bare surfaces: Indoors: Apply 2 - 3 coats.

Outdoors: For avoiding mould and darkening, prime with a coat of Titanxyl Water-Based Lasur Undercoat. Finish with 3 coats of Environmentally-Friendly Wax-Like Varnish.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, lightly sand and directly varnish.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

If they are waxed or in poor condition, thoroughly remove old coats and proceed as on bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Minimize paint waste by buying just the right amount for the recommended coverage rate. Give a new use to spare house paint. Reusing paint can effectively minimize the environmental effects on the life cycle of the products.

Waste is to be placed in municipal waste containers.

Store in tightly closed and identified packs, between 5°C and 50°C.

It is recommended to use goggles and gloves as a protection against splashes, as well as to wear a mask in case of spray application.

Protect the packs from temperatures below 0°C

Issue date: 2016-04

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

INDUSTRIAS TITAN S.A.U.
España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94
Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764



V38 - ENVIRONMENTALLY-FRIENDLY WAX-LIKE ASPECT VARNISH