

DESCRIPCIÓN

DATOS TÉCNICOS

Naturaleza	Epoxy
Acabado	Satin
Color (UNE EN ISO 11664-4)	White and grey.
Densidad (UNE EN ISO 2811-1)	1.45 - 1.50 Kg/l
Rendimiento	1st coat: 5 - 7 m ² /l (70 dry μ), 2nd coat: 8 -10 m ² /l (50 - 60 dry μ)
Secado a 23°C 60 % HR (UNE 48301)	5 - 6 hours
Repintado a 23°C 60% HR (UNE 48283)	Minimum: 12 hours. Maximum: 2 days
Proporción de la Mezcla	Base: 3 parts, Hardener: 1 part
Vida de la Mezcla a 23°C	4 - 6 hours
Métodos de Aplicación	Roller and Airless (The data quoted are only hints)
Dilucion	Roller: 1st coat: 15 - 20%, 2nd coat: 0 - 5%, Airless: Maximum: 5%
Diámetro Boquilla	Airless: 0.018" - 0.021"
Presión Boquilla	Airless: 150 bar
Diluyente	873 Thinner
Limpieza de Utensilios	872 Thinner.
Espesor Recomendado (UNE EN ISO 2808)	70 - 80 dry μ
Condiciones de Aplicación, HR<80%	+10°C - +30°C
Punto de Inflamación (UNE EN ISO 3679)	Base: 28 °C / Hardener: 28 °C

Volumen Sólidos (UNE EN ISO 3233-3) 58 - 60 %

Presentación 10 l, 4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

MODO DE EMPLEO

RECOMENDACIONES GENERALES:

Carefully stir the product in the pack. The surfaces to be painted have to be clean, dry, sound and free from polluting agents, such as oil, grease, whitewash, efflorescence, etc.

SUPERFÍCIES NO PREPARADAS:

Cement and concrete: They have to be thoroughly set (minimum drying: 28 days) . Remove efflorescence or whitewash by water jet. Let to dry before painting. If the surface is too smooth, it will need to be roughened by milling or sandblasting. Clean the surface with dust aspiration equipment. Apply the required number of primer coats until reaching the recommended thickness. Finally apply the coats of finish product following instructions. Other surfaces. Seek advice.

MANTENIMIENTO SUPERFICIES YA PINTADAS EN MAL ESTADO

Remove oil and grease stains, as well as poorly adhered old paint coats or any other polluting agent by using a suitable equipment. Clean the surface with dust aspiration equipment. Patch with this primer the bare areas, preferably by brush. If there is a large bare surface to patch, apply a general coat of this primer. Finally apply the coats of finish product following instructions.

PRECAUCIONES

Always read the pack label before use. For more information, please refer to the Safety Data Sheet. Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use. Paint reuse can effectively minimize environmental effects on the life cycle of products.

Fecha de actualización : 2021-05

Toda Ficha Técnica queda anulada automáticamente por otra de fecha posterior o a los cinco años de su edición. Garantizamos la calidad de nuestros productos pero declinamos toda responsabilidad debida a factores ajenos a la pintura o a una utilización inadecuada de la misma. Ante cualquier duda consulte a nuestros servicios técnicos a priori.