DX-810 / Epoxy Thinner

// Exterior - Interior // Código: X81

DESCRIPCIÓN

Thinner based on a mixture of aromatic hydrocarbons and esters with medium speed curve for the dilution of epoxy paints.

- Suitable for a wide variety of uses.
- High thinning power.
- Thinner suitable for epoxy products and in spray applications at high temperatures (anti-blurring).

DATOS TÉCNICOS

Densidad (UNE EN ISO 2811-1)	0.88 - 0.89 Kg/l
Punto de Inflamación (UNE EN ISO 3679)	29 ºC
Presentación	5 l

MODO DE EMPLEO

PRECAUCIONES

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.
Store in tightly closed containers protected from sources of heat and temperatures below 0ºC. Shelf life: 36 months in original unopened packaging.
Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use. Paint reuse can effectively minimize environmental effects on the life cycle of products.

Fecha de actualización: 2024-03
Toda Ficha Técnica queda anulada automáticamente por otra de fecha posterior o a los cinco años de su edición. Garantizamos la calidad de nuestros productos pero declinamos toda responsabilidad debida a factores ajenos a la pintura o a una utilización inadecuada de la misma. Ante cualquier duda consulte a nuestros servicios técnicos a priori.

INDUSTRIAS TITAN S.A.U.
España: P. I. Pratenc, c/114, 17-19 - 08820 El Prat de Llobregat- T.+34 93 479 74 94
Portugal: Rua Fonte Cova, 51 - 4475-031 Maia. Apartado 2020 - 4476-909 Castelo da Maia T .+351 229 865 450 - F.+351 229 810 764