

## DESCRIPCIÓN

## DATOS TÉCNICOS

Densidad (UNE EN ISO 2811-1)	0.85 - 0.88 Kg/l
Métodos de Aplicación	Brush, Roller and Spray-gun
Dilucion	Brush: 5 - 10%, Spray-gun: 15 - 20%
Punto de Inflamación (UNE EN ISO 3679)	25 °C
Presentación	1 l

## MODO DE EMPLEO

### RECOMENDACIONES GENERALES:

It thins paints quickly. Therefore, it has to be used with care.

Especialmente suitable for paints to be applied by spray-gun. When applying alkyd paints by brush or roller, it is possible to use this thinner, but in limited amounts because it may damage base coats if they are not dry enough.

## PRECAUCIONES

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use. Paint reuse can effectively minimize environmental effects on the life cycle of products.

Fecha de actualización : 2021-05

Toda Ficha Técnica queda anulada automáticamente por otra de fecha posterior o a los cinco años de su edición. Garantizamos la calidad de nuestros productos pero declinamos toda responsabilidad debida a factores ajenos a la pintura o a una utilización inadecuada de la misma. Ante cualquier duda consulte a nuestros servicios técnicos a priori.