

DESCRIPCIÓN

DATOS TÉCNICOS

Naturaleza	Aromatic polyurethane
Acabado	Matt
Color (UNE EN ISO 11664-4)	White
Densidad (UNE EN ISO 2811-1)	1.25 - 1.30 Kg/l
Rendimiento	5 - 6 m ² /l
Secado a 23°C 60 % HR (UNE 48301)	15 minutes touch dry
Repintado a 23°C 60% HR (UNE 48283)	After 1 - 2 hours
Proporción de la Mezcla	Lacquer/Hardener: 2/1
Vida de la Mezcla a 23°C	4 hours
Métodos de Aplicación	Aerographic, airmix, airless and electrostatic spray-gun
Dilucion	Aerographic, airmix, airless: 0 - 5%, Electrostatic: 5 - 10%
Diluyente	MADERLAK Polyurethane Thinner
Limpieza de Utensilios	MADERLAK Cleaning Thinner
Espesor Recomendado (UNE EN ISO 2808)	180 - 220 g/m ²
Condiciones de Aplicación, HR<80%	+20°C - +30°C
Punto de Inflamación (UNE EN ISO 3679)	Base: 10°C, endurecedor: 4°C
Volumen Sólidos (UNE EN ISO 3233-3)	41 - 43%
Presentación	37,5 l, 6 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

MODO DE EMPLEO

RECOMENDACIONES GENERALES:

Carefully stir the contents in the can. Control the product temperature (20°C).

On veneered and massive boards, previously sanded, remove any sanding dust. The coverage data stated in this technical sheet are intended for applying 2 - 3 coats of White Polyurethane Undercoat, with overcoating intervals of 1 - 2 hours between every two coats. Allow 14 - 16 hours before sanding (280 - 320 grit)

PRECAUCIONES

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use. Paint reuse can effectively minimize environmental effects on the life cycle of products.

Fecha de actualización : 2021-05

Toda Ficha Técnica queda anulada automáticamente por otra de fecha posterior o a los cinco años de su edición. Garantizamos la calidad de nuestros productos pero declinamos toda responsabilidad debida a factores ajenos a la pintura o a una utilización inadecuada de la misma. Ante cualquier duda consulte a nuestros servicios técnicos a priori.